



HOUSEWRAP SEAMING TAPE

REX™ Premium Seam Tape is a high strength PET film designed for the toughest conditions with great cold and warm weather applications.

- Formulated with a “quick-tack” adhesive to speed installation
- 3” wide versus standard 2” wide tapes – more surface area to cover seams
- Easy quick tear edges to speed installation
- Excellent initial and long term adhesion
- Excellent chemical and thermal stability



REX™ Premium Seam Tape

PRODUCT SPECIFICATIONS	RESULTS
Backing	Polyester (PET)
Adhesive Material	High Tack Acrylic
Thickness	3.38 mil.
Adhesion (Peel)	60.0 oz./in.
Tensile Strength	20 lbs./in. width
Color	White
Roll Width	3 in.
Roll Length	165 Lineal Feet
Service Temperature	-22°F to 148°F
Application Temperature	-4°F to 105°F

Shelf Life: Recommend one year from date of receipt by customer when stored under optimum conditions. (70°F, 50% RH)
 Note: To the best of our knowledge, these are typical property values and are intended as guides only, not as specification limits. ALPHA PROTECH ENGINEERED PRODUCTS, INC. MAKES NO WARRANTIES AS TO THE FITNESS FOR A SPECIFIC USE OR MERCHANTABILITY OF PRODUCTS REFERRED TO, no guarantee of satisfactory results from reliance upon contained information or recommendations and disclaims all liability for resulting loss or damage.

AlphaProTech Engineered Products, Inc.
 301 South Blanchard St.
 Valdosta, GA 31601
 866-312-1837

Manufacturing & Distribution Facilities
 Valdosta, Georgia
 Nogales, Arizona
 Salt Lake City, Utah

